



# FRONT AND REAR ELEVATION






STEEL

-ALL SCREWS #10, LENGTH PER DRAWING OR AS NOTED


-ALL CONCRETE TO BE 3500 PSI (MIN.)



### **POST-CEMENT BRACKET**

-CUSTOM BRACKET


- -(4) 3/16 DIA.x 5" LONG HEADLOCK SCREWS
- -(1) 1/2" DIA. x 4" LONG WEDGE ANCHOR



# POST-BEAM CORNER BRACKET

-CUSTOM BRACKET

- -(5) 3/16 DIA.x 9" LONG HEADLOCK SCREWS -(6) 3/16 DIA.x 5" LONG HEADLOCK SCREWS




#### **RAFTER-BEAM BRACKET**

-SIMPSON APLH26


- -(4) 1 1/2" BLACK HEAD WOOD SCREWS
- -(4) 2 1/2" WOOD SCREWS

#### POWDER COATED STEEL BRACKETS DETAIL



Site Address





BRACKETS TO BE BLACK POWDER COATED **Building Size** 

**Customer Name** 8x10 Wood 0011 Stuart Tarce Modern Pergola City, State Zip-Code BYS P.O. ##### 111-222-3333



The Backyard Showcase 2604 Lincoln Highway E. Ronks, PA 17572

July 11, 2024

SHEET NO. A-1